As a postdoctoral fellow, Anne Carpenter found herself facing a daunting task: screening *Drosophila* cell cultures for genes affecting cell growth using a library of over 22,000 inhibitory RNAs. With the RNAs pre-printed on microscope slides, she plated cultured fly cells atop the library to induce RNA interference. Three days later, she stained the cells to visualize their size and cell cycle status.

It was then she encountered a problem: With replicates, the experiment included nearly 90,000 conditions. “I needed to process tens, probably hundreds of thousands of images, but couldn’t find software that was up to the task,” recalls Carpenter, who is now Director of the Imaging Platform at the Broad Institute of Harvard and MIT. That’s not to say there were no tools available—some could handle the volume of images but not the subtlety of the work; others could handle the science but not the number of pictures.

Carpenter’s story is not unique. Today’s laboratory hardware—whether microscopes, mass spectrometers, or DNA sequencers—produce data by the gigabyte (GB). Yet, they typically lack the software necessary to handle, process, and extract meaning from those data, at least for the most interesting bleeding-edge applications. But researchers have stepped in to bridge that gap, producing freely available computational tools for experts and neophytes alike, empowering them to squeeze biological insights from raw data.

How big is “Big Data”?

Adina Howe was a postdoctoral fellow at Michigan State University with C. Titus Brown (now Associate Professor of Genetics at the University of California, Davis) when she found herself trying to assemble bacterial genomes from metagenomics data sets so large—nearly 400 billion bases worth—that the assembler software couldn’t keep up. “They would require hundreds of gigs of memory that we didn’t have,” she explains.

Typically, a raw next-generation sequencing data set is ~30 GB per sample—an order of magnitude smaller than Howe’s. Yet even at that size, a computing neophyte would encounter significant practical difficulties—moving the data from place-to-place or even figuring out how to open the files takes savvy. “They can’t open it any Microsoft product,” Howe notes, as the software would likely crash. And of course, processing the data—filtering out low quality sequences, for instance—would be even more difficult.

Fortunately, Brown had been developing tools to handle such problems for years. His lab’s flagship software is “khmer,” a tool that reduces sequences into a series of arbitrary-length “words” (that is, k-mers), simplifying tasks such as genome assembly.

To tackle Howe’s metagenomics problem, Brown’s team implemented a probabilistic data structure called a “Bloom filter,” which reduces the amount of memory required for sequences some 40-fold. As Howe explains it, this structure is like a faculty mailroom in which each box is shared by several instructors. By creating multiple “rooms” in which those faculty pairings are shuffled, it becomes statistically possible to determine how likely it is that any given individual has mail—in this case, an overlapping sequence to fit into a growing assembly—by checking to see if those different boxes are full.

“I go to my mailbox and I ask, ‘Hey, are any potential connecting sequences stored in my data structure?’ If not, I know that they don’t exist, and I don’t have to pursue that path any more; otherwise, I’m going to check my other ‘mailbox rooms’.”

In the end, Howe used this approach to produce an assembly of nearly 5.5 million protein-coding genes from her metagenomics data set.

“It took us a good frustrating year,” Howe, who now is an Assistant Professor of Agricultural and Biosystems Engineering at Iowa State University, recalls.

Imaging's big challenge

Pavel Tomancak, a group leader at the Max Planck Institute of Molecular Cell Biology and Genetics, faces a similarly daunting problem in his research. He studies gene expression during *Drosophila* embryogenesis, generating multi-terabyte recordings of fruit fly embryos via light-sheet microscopy that he mines to trace cellular motion during development. With 24 hours worth of images recorded from multiple angles and taken several times a second—existing software simply cannot keep up. “They are not adequate; they are not precise enough; they are not able to follow hundreds of thousands of cells without making any mistakes.”

Tomancak is one of the core developers of the Fiji project. Fiji is a popular “distribution” of the open-source imaging software ImageJ that includes not only the core ImageJ software but also key plugins, a scripting language, an updater, and more. ImageJ is popular in its own right, but most microscopists use Fiji, according to ImageJ developer Wayne Rasband, who first began development on the tool in 1997. According to Tomancak, some 50,000 computers routinely ping the software’s update server nearly daily.

To solve his big-data problem, Tomancak has been developing a series of new Fiji plugins. One, BigDataViewer, allows users to view and interact with massive data sets remotely, rather than downloading the data. “You just simply cannot have 10 terabytes of image data on your laptop,” he says. He plans to use this software to drive crowdsourcing initiatives in which researchers annotate each other’s data, thereby making downstream machine-learning algorithms far more effective.

Anne Carpenter learned how to program in order to deal with large experimental data sets. Credit: Maria Nemchuk, Broad Institute.

The Ilastik (Interactive Learning and Segmentation Toolkit) package implements machine learning algorithms to automate object segmentation, classification, and tracking in microscopy images. By applying brush strokes (bright red) to identify features that are or are not of interest, the software learns (and predicts) which pixels in the 3-D image correspond to a cell. Credit: A. Kreshuk.

What might the sequencing community learn from projects such as Fiji? According to Tomancak, the question is actually backwards: even though the microscopy community has been developing software longer than geneticists, there is much they can learn from their younger cousins, especially in regards to bioinformaticians’ open-source ethos and spirit of collaboration—two lessons the Fiji community has taken to heart.

For instance, Fiji developers organize regular “hackathons” to collaboratively improve the software. “We fly developers from all over the world to one place, put them in a room with internet access and lots of coffee, and they program together for a week or two.” The result is typically a burst of innovative new plugins and features. After a 2012 hackathon in Dresden, developers pushed out a Fiji plugin called imgLib that effectively allows developers to interact with image data the same way regardless of data type, size, or location. “This is a library that allows professional software developers to develop their code really efficiently and make it run fast,” he says.

In the case of Carpenter’s *Drosophila* cells, there was another issue she had to overcome. “I had basically zero computer

science experience when I began the project,” she says. At first, she considered trying to develop a plugin for ImageJ, “but it quickly became clear that a new architecture was needed for this high-throughput case, which would require a computing cluster.”

Carpenter wanted to turn high-throughput visual data into numbers. Suppose a researcher was given 2 sets of images in which the nuclei differed in size by 10% on average, but with a lot of heterogeneity within each population. Even an expert might fail to spot the difference, she says: “The human brain is just not tuned to pick up on that sort of thing, whereas it’s trivial for a computer.”

So, Carpenter decided to try her hand at the high-level mathematical language MATLAB. Armed only with online manuals and, eventually, a 1-day introductory course, she started producing ever-more-sophisticated pipelines to segment images into discrete objects and quantify those objects, ultimately producing a package called CellProfiler. Published in 2006 and overhauled by a professional software engineer in 2011, the software has generated more than 3000 citations to date, she says. An accompanying tool, CellProfiler Analyst,

CellProfiler was created by Anne Carpenter to segment and quantify discrete objects in microscopy images. Credit: A. Carpenter.

uses machine-learning algorithms, in which researchers “train” the software to recognize objects of interest, to automate those processes.

“I loved programming right away,” Carpenter says. “In contrast to working with cells, the computer does exactly what you tell it to do, and it does the same thing every time. I loved that investing some time in creating an image processing algorithm saved so much time and tedium for my project.” She attributes the software’s success to the fact that its design and interface were created by “a working biologist who specialized in microscopy.” But another reason for its popularity could be that it, like most researcher-produced data analysis software, is open source, enabling third-party developers to contribute to and improve the code. “Certainly a strong motivation for us in making CellProfiler open-source was to bring these kinds of powerful tools into the hands of researchers anywhere,” she says.

Conducting change

Carpenter’s experience notwithstanding, computational neophytes cannot always easily pick up programming. Though software tools are often easily extended and configured with macros and plugins,

there’s a world of difference between simple scripting and full-blown programming. More sophisticated computational challenges are frequently tackled by true software engineers rather than microscopists or geneticists. For instance, the *ilastik* (Interactive Learning and Segmentation Toolkit) package, which implements machine learning algorithms to automate object segmentation, classification, and tracking in microscopy images, is supported by three full-time developers and a number of part-time researchers, says Anna Kreshuk, a senior scientist and core developer on the project.

Similarly, the community-driven Bioconductor project has dedicated staff members who work to inject some much needed programming expertise into user-provided packages, says Wolfgang Huber, a principal investigator at the European Molecular Biology Laboratory in Heidelberg.

Built using the statistical programming language R, Bioconductor is a collection of more than 1100 software modules for analyzing DNA sequence, microarray, flow cytometry, and imaging data, among other tasks.

“The key idea behind R and Bioconductor is turning users into devel-

opers,” Huber says. Researchers—who Huber calls “domain experts”—develop custom solutions for their particular problems that could actually be generically useful. “I think that’s the key to why the project is so successful,” he explains, “The software is written by biologists who solve real scientific problems.”

But the downside of this approach is that biologists are not software engineers. As a result, Huber and his colleagues on the Bioconductor “core team” sometimes advise and provide code to make tools more robust and efficient, playing a role “more akin to reviewers and editors.”

Martin Morgan, Associate Member of the Roswell Park Cancer Institute in Buffalo, NY, who directs the Bioconductor project, says that despite their obvious differences, sequencing and microscopy data analysis tools actually have much in common. In particular, both are focused on the problem of data reduction—the conversion of massive raw data files into more manageable pieces suitable for computational analysis.

Take *GenomicRanges*, for instance. Developed in Morgan’s lab, this Bioconductor package allows programmers to generalize sequence analysis by reducing it to computations on a series of genomic intervals—simple pairs of integers that define the start and stop points of a given feature. “*GenomicRanges* represents both the data—the reads that have been aligned to a reference genome—and also the annotation or biological context,” he says. Almost any sequencing data can be represented in this fashion, including ChIP-seq peaks, promoter locations, tran-

Adina Howe needed to develop new software solutions to deal with the large microbial data sets she was studying. Credit: Dana Woolley, Iowa State University.

script counts, and SNPs. As a result, it becomes far simpler to perform computations on those data, such as identifying those promoters that contain a binding site for a particular protein. “It kind of channels your research questions. It helps you to pose questions that are computationally tractable.”

The Bioconductor core team developed the package to alleviate data overload. Researchers, Morgan says, “were really overwhelmed with the volume of data that was being produced by these sequencers, and all of the computational expertise in the early days was focused on managing the large data. Few people realized the value of working with data in a more reduced fashion, a more abstract fashion.”

Today, nearly 125 Bioconductor packages depend on GenomicRanges, and even more import the package. Gviz, for instance, uses the GenomicRanges architecture to provide a mechanism for graphically visualizing genomic elements—a tool one could use to build a new genome browser, for instance.

Wolfgang Huber, principal investigator at the European Molecular Biology Laboratory in Heidelberg, is involved in the advancement of the Bioconductor project. Credit: EMBL

Morgan attributes Bioconductor's success to three factors. First, he says, it is a group effort. “There was kind of a critical mass of people from the beginning who were collaborating, as opposed to a Lone Ranger out on the plains hoping to make a brilliant insight.” Second, the project has also remained relatively

focused on one overarching problem: analyzing high-throughput genomic data. And finally, there was discipline. “Relative to other similar projects, Bioconductor has a high level of commitment to ... software that's, say, better than average,” he says.

Finding the right course

For those researchers interested in scientific programming, there is no shortage of options, from online tutorials and manuals to forums such as StackOverflow, as well as online courses from such sites as Codecademy. Researchers can even arrange to have a Software Carpentry course at their university.

According to executive director Jonah Duckles, Software Carpentry courses last 2 days and typically include 3 main modules covering the UNIX command line; programming in R, Python, or MATLAB; and version control.

After only 2 days, says Howe, it would be wrong to call attendees experts on any covered topic—they can, for instance, write relatively simple “scripts”—small collections of commands to, say, iterate a series of tasks over a collection of files—a far cry from programming a full-fledged application from scratch.

But the courses do provide a foundation for knowing what's possible to do on a computer and the confidence to seek out additional information to plow through a problem, says Howe. “Before they come to class, they don't know what they don't know,” seconds Qingpeng Zhang, a postdoctoral fellow and bioinformatician at the Joint Genome Institute, who was a graduate student in Brown's lab and also runs Software Carpentry courses.

Data analysis is a laboratory method like any other, Howe notes. “The first thing I learned in the wet lab was how to grow bacteria in a sterile environment, I couldn't have done that on my own, someone had to teach it to me.” Computation is no different. “Everybody needs somebody to train them at some point for almost everything we do. And then you have to go and do it yourself and make mistakes, but that's just part of the process.”

Written by Jeffrey Perkel, Ph.D.

BioTechniques 60:108-112 (March 2016)
doi: 10.2144/000114386

www.BioTechniques.com

Gene Codes Corporation

T C A G E N E
A G T C O D E S

SEQUENCHER® 5.4.1

Software for Sanger and NGS
DNA Sequence Analysis
with RNA-Seq

Download today!
visit www.genecodes.com

Power with Simplicity